

# Paraty

[www.cobsa.net/paraty](http://www.cobsa.net/paraty)


since 1976




# Paraty

since 1976


5x15 cm - 2x6 in  
10x10 cm - 4x4 in



Preto



Verde Floresta



Azul Puro




Amarelo




Cinza



Verde Cha



Azul Bondi



Coral



Branco Gloss



Branco Matt



Pasta Blanca - *White Body*



Brillo - *Gloss*



Variación Moderada - *Moderate Variation*

## Embalaje / Packing

Formato Size	Espesor Thickness	CAJA / BOX			PALET / PALLET			
		Piezas Pieces	Kg	m2	Cajas Boxes	Piezas Pieces	Kg	m2
5x15 cm	9 mm	102	14,20	0,77	64	6.528	909	48,96
10x10 cm	9mm	66	11,20	0,66	96	6.336	1.112	63,36



1976

*Paraty, BRANCO MATT + BRANCO BRILLO*





since 1976

ALDO

*Paraty, AZUL PURO*





since 1976

ESPOS

*Paraty, AZUL BONDI*





since 1976

# DESIGN

Paraty, VERDE CHA





since 1976

DESIGN

*Paraty, CORAL*



# Paraty

## RECOMENDACIONES / RECOMMENDATIONS

**Colocación:** Es necesario emplear un material de agarre y de rejuntado apropiado para cada producto

Hay que realizar un planteamiento inicial antes de empezar la colocación y tener en cuenta el tipo de junta, estructural, perimetral, dilatación y colocación que debe utilizarse para cada uso.

Aconsejamos que para obtener un resultado óptimo se debe utilizar una junta de 1,5 mm.

**Tile Fixing:** It is necessary to use an appropriate adhesive and grouting material for each product

An initial approach must be made before starting the installation and take into account the type of joint, structural, perimeter, expansion and installation that must be used for each use.

We advise that to obtain an optimal result a 1.5 mm joint should be used.

**Mantenimiento y Limpieza:** Una vez terminada la colocación se recomienda eliminar los restos de material adhesivo y rejuntado específico para cada material siguiendo las instrucciones del fabricante de estos productos.

En la limpieza general no debe de emplearse detergentes en polvo y estropajos agresivos. Es suficiente limpiar los azulejos con una esponja, agua tibia y un jabón líquido neutro. Finalmente aclarar con agua limpia.

Maintenance and Cleaning

**Once the placement is finished:** it is recommended to remove the remains of adhesive material and specific grouting for each material, following the manufacturer's instructions for these products.

In general, powder detergents and aggressive scouring pads should not be used for cleaning. It is enough to clean the tiles with a sponge, warm water and a neutral liquid soap. Finally, rinse with clean water.

SIZE: 5X15 cm / 2X6" 10x10 cm / 4x74"	THICKNESS (mm): 9mm	GROUP BIII: Wall Tile
---	------------------------	--------------------------

Size, Thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requirements
---	--------------	----------------------------------

Water absorption capacity	EN ISO 10545-03	> 10%
Flexion resistance	EN ISO 10545-04	≥ 10 N/mm <sup>2</sup>
Thermal shock resistance	EN ISO 10545-09	It stand the test
Cracking resistance	EN ISO 10545-11	It stand the test

Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 19545-13	GLA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5



COBSA

COBSA FACTORY

Calle San Fernando 7,  
12200 Onda, Castellón  
Spain

Tel.: +34 964 57 78 78

a brand of

**ALTOGLASS**  
GROUP

HEADQUARTERS

Pol. Ind. Casablanca s/n  
12593 Moncofa, Castellón  
Spain

Tel.: +34 964 57 78 78  
alttogglass@alttogglass.com

USA BRANCH

1924 - 28 NW 82 Avenue  
Doral FL. 33126  
USA

Tel.: +1 305 - 718 8682  
info.usa@alttogglass.com

[www.cobsa.net/paraty](http://www.cobsa.net/paraty)

since 1976

